

Slidio

Simplicity, quality and ease of use all rolled into one

Discover the new Slidio sliding wall and get optimum space re-configurability.



Set up in one single movement

It takes just one single hand movement to set up or park the entire Slidio sliding wall. This saves you lots of time, because there is just one manoeuvre involved. The wall is also available as a 2-wing version so that the wall can cover an even greater width. The larger version is equally easy to operate.

For what kind of spaces?

The Slidio sliding wall gives you the comfort, ease of use and quality that Espero stands for. This is the ideal wall system when you need a movable wall that lets you open up spaces quickly, but do not have sufficient space for a large wall system. Sliding walls are often used at schools to turn a space into 2 separate classrooms. You can also find them at libraries, office buildings and banks.



Discover our Sliding Walls

The Slidio is available in various versions. This movable wall can be supplied with glass or various other finishes, with or without sound insulation and with visible or concealed profiles. We have the right solution for any space. Take a look at all the versions.

Specifications Type 100 - 110

The Slidio is available in various versions. This movable wall can be supplied with glass or various other finishes, with or without sound insulation and with visible or concealed profiles. We have the right solution for any space. Take a look at all the versions.



Type 100 Glas



Type 100 Wood



Type 110 Wood

	100	100	110
Version	Glass	Wood	Wood
Profiles	Visible	Visible	Concealed
Thickness	107 mm	107 mm	119 mm
Wall height	Up to 3000	Up to 3000	Up to 3000
Max. wing length:	1500 mm	5224 mm	5176 mm
C2C certification	Bronze		
Plating	Glass	superPan with FSC certification.	superPan with FSC certification.
Finish	All materials commonly used in interior construction are available. In addition: mirrors, textiles, acoustic cassettes, etc.		
Sound insulation Rw rating (laboratory value)	Up to 50 dB*	Up to 50 dB*	Up to 50 dB*
Weight	Max. 500 kg	Max. 500 kg	Max. 500 kg
Colour of profiles	Standard anodised aluminium, available in all colours		
Available with door	No	No	No
Operation	Semi-automatic operation. A press of the button retracts or releases the top and bottom seals.	Semi-automatic operation. A press of the button retracts or releases the top and bottom seals.	Semi-automatic operation. A press of the button retracts or releases the top and bottom seals.
Supported by:	Standard: weight supported by upper track.		
Track and wheels	Bearing-mounted hard-plastic wheels that run along the hard-aluminium track profile.		
Environmental requirements	Only suitable for indoor use. Relative humidity of 60% should not be exceeded.		

* other specifications available on request

Specifications Type 65 - 45

The Slidio is available in various versions. This movable wall can be supplied with glass or various other finishes, with or without sound insulation and with visible or concealed profiles. We have the right solution for any space. Take a look at all the versions.



Type 65 Glass



Type 65 Wood



Type 45

	65	65	45
Version	Glass	Wood	Glass
Profiles	Visible	Visible	Visible
Thickness	65 mm	67 mm	45 mm
Wall height	Up to 3000 mm	Up to 3000 mm	Up to 3000 mm
Max. wing length	3800	3800	4m ² (depending on the wall height)
C2C certification	Bronze		
Plating	Glas	superPan with FSC certification.	Glas
Finish	All materials commonly used in interior construction are available. In addition: mirrors, textiles, acoustic cassettes, etc.		
Sound insulation Rw rating (laboratory value)	40 & 42	Up to 46 dB*	N/A
Weight	35 kg/m ²	19-32 kg/m ²	25 kg/m ²
Colour of profiles	Standard anodised aluminium, available in all colours		
Available with door	No	No	No
Supported by:	Standard: weight supported by upper track. Floor supported version optional.	Standard: weight supported by upper track. Floor supported version optional.	Standard: weight supported by upper track.
Track and wheels	Bearing-mounted hard-plastic wheels that run along the hard-aluminium track profile.		
Environmental requirements	Only suitable for indoor use. Relative humidity of 60% should not be exceeded.		

* other specifications available on request

Parking Situation and Finishes

The Slidio sliding wall can be parked both in front of the wall or in the compartment. The latter option is ideal because it does not require a parking situation. Aside from that, our sliding walls are available with a glass or various other finishes, including melamine, leather or fabric. Give your wall the finish you want with a neutral colour or bring your space to life with a vibrant colour. Choose a glass finish when you want an industrial Crittall effect, for example. The possibilities are endless. For more information, download our colour brochure or contact us.



Colour Brochure

2021 ESPERO Brochure Colours and Designs.pdf